

BAC 55



Features	BAC 55
Outer dimensions in mm	600 x 500 x 580 height
Inner dimensions in mm	415 x 315 x 410 height
Volume	53 litres
K value	0,38 W/m ² .K
Weight	16 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

Specifications and optional equipment



Technical features

- 1 Body and door made of one piece rotomoulded polyethylene. Insulation with CFC free expanded polyurethane foam.
- 5 One-piece EPDM tubular seal.
- 6 Label holder
- 10 Hinging from moulding and 115° lid opening.
- 11 Flush mounted and recessed fastener
- 13 Stackable Bac 55 with embossed bottom and lid from moulding.
- 15 Integrally moulded handles

Standard equipment

- B Eutectic plate support

Optional equipment

- A 2 eutectic plates TOP 55
 C Dry ice drawer
 N Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm
 O Castor base fitted with 2 fixed and 2 swivelling wheels ø 100 mm with brake
 P Castor base fitted with 4 swivelling wheels ø 100 mm, 2 with brake.
 S Silicone seal

kwaliteit koelt klasse!

Coldvink

Tel. +31 184 642101 * www.coldvink.nl