

## ROLL 220

NEW WAVE OF COLD



Features	ROLL 220
Outer dimensions in mm	600 x 800 x 1130 height
Inner dimensions in mm	430 x 620 x 830 height
Volume	221 litres
K value	0,34 W/m <sup>2</sup> .K
Weight	60 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

## Specifications and optional equipment



### Technical features

- Body and door made of one piece rotomoulded polyethylene. Grooves on internal walls facilitate cold gas flow natural convection
- Body/door hinging with 2 pins
- 1-point « Pelican » closing system, made of rustproof treated steel.
- Rustproof treated steel frame, flush mounted, fitted with 2 fixed and 2 swivelling castors Ø 100 mm
- One-piece EPDM seal. Retracting door stop to keep door fixed open.
- Label holder
- Flush-mounted handles

### Standard equipment

B Eutectic plate support

### Optional equipment

- A Eutectic plate TOP 370  
 C Dry ice drawer  
 D SIBER SYSTEM® Tank for chilled products or frozen products  
 E Thermometer  
 F 2 brake wheels ø 100 mm  
 or 4 wheels ø 125 mm  
 2 brake wheels ø 125 mm  
 G 4 metal feet ø 60 mm  
 H 1 removable shelf plastic coated with inox support  
 I 1 removable shelf stainless steel with inox support  
 K Metal top rail

*kwaliteit koelt klasse!*

# ColdVink

Tel. +31 184 642101 \* [www.coldvink.nl](http://www.coldvink.nl)

## ROLL 220 Catering

NEW WAVE OF COLD



Features	ROLL 220
Outer dimensions in mm	600 x 800 x 1130 height
Inner dimensions in mm	430 x 620 x 830 height
Volume	221 litres
K value	0,32 W/m <sup>2</sup> .K
Weight	66 Kg
Insulation material	Expanded polyurethane foam
Material of the walls	Rotomoulded polyethylene

## Specifications and optional equipment



### Technical features

- Body and door made of one piece rotomoulded polyethylene. Grooves on internal walls facilitate cold gas flow natural convection
- Body/door hinging with 2 pins
- 1-point « Pelican » closing system, made of rustproof treated steel.
- Rustproof treated steel frame, flush mounted, fitted with 2 fixed and 2 swivelling castors Ø 100 mm
- One-piece EPDM seal. Retracting door stop to keep door fixed open.
- Label holder
- 4 flush-mounted handles

### Standard equipment

- B Eutectic plate support
- L Stainless steel rack for 600 x 400 or Gastro 1/1 trays. 9 levels

### Optional equipment

- A Eutectic plate TOP 370
- C Dry ice drawer
- E Thermometer
- F 2 brake wheels ø 100 mm or 4 wheels ø 125 mm
- G 4 metal feet ø 60 mm
- J Metal top cage
- K Metal top rail
- T Towing system, foldable sprung tow bar made of stainless steel with 4 wheels Ø 160
- U Dry ice polyethylene tray

*kwaliteit koelt klasse!*

# COLDVINK

Tel. +31 184 642101 \* [www.coldvink.nl](http://www.coldvink.nl)